


HOT-AIR CENTRIFUGAL DRYER



Gentle drying thanks to regulated starting speed



POLYSERVICE
PRECISION IN FINISHING

POLYSERVICE AG
Lengnaustrasse 6
CH - 2543 Lengnau
Tel. +41 (0)32 653 04 44
Fax +41 (0)32 652 86 46
www.polyservice.ch

SPECIAL FEATURES OF THE POLYAIR

POLYAIR



- No damage to the piece goods thanks to regulated starting and braking speeds
- No deformation of precision parts thanks to 5 pre-selectable speeds (200–1000 rpm)
- Stainless drying thanks to optimum hot-air circulation in the processing zone
- No floor anchorage necessary thanks to vibration-damping rotor suspension
- Internal heater temperature individually adjustable by means of thermostat (20–100°C)
- Automatic lid opening at end of working time

Technical data

Max. charge	50 kg
Speeds	200/400/600/800/1000 1/min
Electrical connection	400 VAC/50 Hz
Fusing	16 A
Output	6 kW
Dimensions (W × D × H)	710 × 970 × 950/1195 mm
Weight	335 kg

POLYAIR accessories



Standard basket

Charge basket in galvanised, perforated sheet steel, perforation \varnothing 2mm



Star insert, 4 compartments

Star-shaped charge frame, 4 compartments; 4 baskets, \varnothing 140mm, in galvanised, perforated sheet steel, perforation \varnothing 2 mm; 4 fine charge baskets, \varnothing 140 mm, in stainless steel mesh, perforation 0.36×0.20 mm



Star insert, 6 compartments

Star-shaped charge frame, 6 compartments; 6 baskets, \varnothing 100mm, in galvanised, perforated sheet steel, perforation \varnothing 2 mm; 6 fine charge baskets, \varnothing 100 mm, in stainless steel mesh, perforation 0.36×0.20 mm