


CENTRIFUGAL DISC FINISHING MACHINES



The high-performance machine for cost-effective deburring and burnishing of precision parts

POLYDISC 35/60



POLYSERVICE
PRECISION IN FINISHING

POLYSERVICE AG
Lengnaustrasse 6
CH - 2543 Lengnau
Tel. +41 (0)32 653 04 44
Fax +41 (0)32 652 86 46
www.polyservice.ch

SPECIAL FEATURES OF THE POLYDISC 35/60

POLYDISC 35



- Menu-guided microprocessor control with input panel for programming of work processes
- Suitable for wet machining processes
- Integral compound-water metering mechanism
- Device for regulation of water level in the work container
- Easily replaceable slip rings (expendable part)
- Abrasion-resistant container coating

Technical data

	POLYDISC 35	POLYDISC 60
Container volume	35 l	60 l
Charge	24 l	50 l
Piece volume	6 l	10 l
Min. piece size	0.5 mm	0.6 mm
Speeds	20-250 1/min	20-250 1/min
Electrical connection	400 VAC/50 Hz	400 VAC/50 Hz
Fusing	16 A	16 A
Output	1.8 kW	2.2 kW
Dimensions (W × D × H)	1252 × 1019 × 1680 mm	1252 × 1019 × 1680 mm
Weight	320 kg	332 kg

POLYDISC 60

